



# Coliseum C170

8-inch Mini Series Speaker

## Features:

- ▷ 100 Watt Mini Series Speaker
- ▷ 90° x 90° HF Driver
- ▷ 8-inch Woofer with 1-inch Mylar Dome Tweeter
- ▷ Cabinet is Available In Either a White (C170W) or Black (C170) Finish
- ▷ Integrated 70-Volt 'Matching Transformer'
- ▷ 60 to 20,000 Hz Frequency Response
- ▷ 1 x 1/4-inch / Dual Binding Post Inputs
- ▷ Injection Molded, ABS Plastic Cabinet Construction
- ▷ Two-year Unconditional Warranty\*

\*Warranty valid in Canada and the United States only



## Overview:

The integrated 70V 'matching transformer' allows multiple C170's to be connected together without danger of overloading the power amplifier due to impedance drop. The user has a choice of three sensitivity settings (6W, 12.5W, 25W or bypass) selected via a rotary switch located on the rear panel of the speaker, allowing convenient adjustment of the relative volumes of multiple interconnected cabinets.

The C170 is based on the already popular C110, C120 and C130, which have a complete list of features that make them an extremely good value for fixed installations. The C170, is a compact 100-watt loudspeaker made from an ABS plastic enclosure with an 8-inch driver and 1 inch Mylar tweeter, and features both dual binding posts and 1/4" connectors for maximum versatility.

The trapezoidal shape makes the C170 ideal for install or array mounting in tight locations. Shipped with a rugged U-bracket for wall or ceiling mounting, they are a very versatile and cost-effective solution where superior sonic quality is required for small installations, or as a repeater or fill cabinet in larger venues. An optional polemount adaptor (C170ADAPT) is also available for applications where placing the C170 on a speaker stand is required. The C170 is also available in white as the C170W, for situations where a more discreet speaker is required.

## C170 Specifications:

Model	C170 / C170W
SYSTEM TYPE	2-Way
ACTIVE OR PASSIVE	Passive
IMPEDANCE	8
SENSITIVITY (dB @ 1W / 1M)	93
PROGRAM POWER (watts)	100
MAXIMUM SPL (dB)	113
FREQ. RESPONSE (Hz +/- 3dB)	60 - 20000
DRIVER CONFIGURATION	8" / 1" dome tweeter
HF DRIVER(S)	1" Mylar Dome Tweeter
LF DRIVER(S)	8"
TOTAL POWER (watts)	100
COOLING SCHEME	-
POWER CABLE	-
POWER SWITCH	-
INPUTS	1 x Binding Post
INPUTS - 1/4" Jacks	1 x TRS
MIXER CONTROLS	-
OTHER CONTROLS / FEATURES	-
FEET	Yes
INCLUDED HARDWARE	Mounting Bracket
OPTIONAL HARDWARE	Pole Mount Adaptor (1 3/8"-3.5cm) (C170ADAPT)
ENCLOSURE MATERIALS	ABS Plastic
OPTIONAL FINISH	White (C170W)
GRILLE	Perforated Metal
DIMENSIONS (DxWxH inches)	11 x 9 x 16
DIMENSIONS (DxWxH cm)	28 x 23 x 41
WEIGHT (lbs/kg)	14.5 / 6.6

